

Fastening Systems for Atlas EnergyShield® Products



Thermal-Grip® ci Prong Washer

- 2" dia. solid cap washer for use with Grip-Deck® ci screws.
- Pre-spotting prongs for easy on-the-wall screw assembly
- Flattens on surface of the insulation without tearing facer
- Optional labor-saving Grip-Lok® auto-feed system available

Plasti-Grip® ci Prong Washer

- 1-3/4" dia. washer for use with Grip-Deck® ci screws
- Pre-spotting prongs for easy on-the-wall screw assembly
- Compatible with screws and nails. SHOOT IT, SCREW IT, NAIL IT!
- Flexible perimeter reduces tearing of insulation facer

Grip-Deck® ci Screw

- Self-drilling or HiLo threads available for steel or wood studs
- Exterior ceramic coating for corrosion resistance
- Lengths available from 1 5/8" - 6"

Plasti-Grip® PMF Anchor

- Insulation attachment to masonry substrates
- Simple installation. Pre-drill hole, then tap flush with hammer
- Plastic design reduces thermal-bridging
- No screws or adhesives required

Thermal-Grip MVA® Masonry Veneer Anchor

- Air & water penetration resistance
- Thermal-break performance
- Labor & cost savings - Made in USAs

Thermal-Grip TubeSeal™

- Seals blind fastener penetrations of a WRB or air-barrier
- Available in multiple lengths for various insulation thicknesses
- UV resistant polyurethane tube construction is suitable for all weather climates

*Patented or patent pending

TRUFast

130 Graham St. SW
Grand Rapids, MI 49503
(616) 454-3100


wallssales@trufast.com
www.trufastwalls.com



Fastening Systems for Atlas EnergyShield® Products




THERMAL-GRIP® ci Prong Washer



THERMAL-GRIP® ci Prong Washer

1. Specified fastener spacing of 16" x 16" in the field and every 12" around doors, windows and perimeter
2. Pre-spotting prongs for easy "on-the-wall" screw assembly
3. Compress washer until flat. Do not overdrive

PLASTI-GRIP® PMF




PMF Size	Insulation Thickness
2"	½" - ¾"
2 ¾"	1" - 1 ½"
3 ½"	1 ½" - 2"
4 ½"	2 ½" - 3"
5 ¾"	3 ½" - 4"

PLASTI-GRIP® PMF Anchor

1. Recommended fastener spacing of 24" x 24" or dependent on short & long term exposure.
2. Simple installation
3. Pre-drill with 5/16" dia. masonry bit, then tap flush with hammer
4. No pins, screws or adhesives required

THERMAL-GRIP MVA®



THERMAL-GRIP MVA® Masonry Veneer Anchor

1. Typical spacing of 16" x 16" (Check with local building codes)

*Patented or patent pending

*****Images are for general illustrations only.
Consult with the manufacturer to assure
building code compliance.

TRUFast

130 Graham St. SW
Grand Rapids, MI 49503
(616) 454-3100

wallssales@trufast.com
www.trufastwalls.com

