

Fastening Systems for Spiderlath



Grip-Plate® Lath & Plaster Washer

- Large 1 ¼" diameter provides excellent holding power
- Flattens on surface of SpiderLath for flush troweling surface
- Compresses on the SpiderLath and foam strip to help seal the screw penetration against air and moisture
- Can be installed with bulk screws or with Grip-Lok® auto-feed system for rapid attachment



Grip-Deck® ci Screw

- Self-drilling or HiLo threads available for steel or wood studs
- Exterior ceramic coating for corrosion resistance
- Lengths available from 1 5/8" - 6"



Grip-Lok® Autofeed Fastening System

- Labor-saving tool for attaching insulation to wood or steel stud
- Adjustable depth control to ensure proper washer compression
- For use with collated Grip-Deck® ci screws up to 3" length



*Patented or patent pending



130 Graham St. SW
Grand Rapids, MI 49503
(616) 454-3100



wallssales@trufast.com
www.trufastwalls.com



Fastening Systems for Spiderlath



GRIP-PLATE® Lath & Plaster Washer



GRIP-PLATE® Lath & Plaster Washer

1. Specified fastener spacing of 6" x 16" in the field
2. Use with Grip-Deck® ci screws
3. Use with Grip-Lok® Autofeed Fastening System for rapid attachment

*Patented or patent pending



130 Graham St. SW
Grand Rapids, MI 49503
(616) 454-3100

wallsales@trufast.com
www.trufastwalls.com

