



## SHEATHING ATTACHMENT. GALVANIZED STEEL.

Low profile galvanized steel washer can be used with either Grip-Deck® bugle head screws or pins/nails to secure various sheathing materials including exterior gypsum sheathing, wood sheathing, cement board sheathing, MgO board, etc. The Washer helps prevent overdrive of the fastener head and pull-through of the fastener head through the sheathing outer surface, which is critically important when the sheathing layer is integrated with the weather resistive layer or air barrier.

### PRODUCT FEATURES

- 1.25" dia.
- Galvanized steel
- Low profile (.25" or about the thickness of a credit card)
- Dome shape flattens on the surface of the sheathing
- Use with screws or nails
- Solid cap washer design

\*Patented or patent pending.



### AVAILABLE WITH BULK OR COLLATED GRIP-DECK® SCREWS

Use with Grip-Lok® Autofeeder Fastening System with Bullseye® nose adaptor for rapid attachment.

Grip-Deck® Self-Drilling or HiLo Thread Screws available in bulk or collated.



SINCE 1823

ALTENLOH, BRINCK & CO. US, INC.  
ALTENLOH, BRINCK & CO. - GROUP

**TRUFAST**  
WALLS

130 Graham St. SW, Grand Rapids, MI 49503 • 616-454-3100 • wallssales@trufast.com • www.trufastwalls.com

Bulletin No. TFW-2012